

SPECIFICATION FOR NEOPRENE TANK



	6m ³	15m ³
Capacity	6000 L	15000 L
Height	155 cm	155 cm
Diameter	282 cm	431 cm
Dry Weight	25 kg	30 kg
Packed Size	100 x 60 x 60 cm	104 x 62 x 60 cm

Description: Our range of open top neoprene storage tanks are light and low volume when empty. During filling the fabric structure self-elevates and assumes a very stable configuration even in high winds. No tools or support structure are required, making them a first choice emergency or long term liquid storage facility. The range may be used under any climatic conditions, and applications include oil spill recovery, firefighting, pressure washing and water storage.

Construction: Reinforced double faced 900 gm² neoprene fabric vulcanised under pressure to guarantee seam integrity. The tank is fabricated with an inflatable air filled collar for extra stability.

Accessories Included: A central internal stainless steel lifting ring is provided for use during cleaning operations. All tanks are fitted with external stainless steel, top cover restraint rings. All sizes are supplied with an integral 2" ball valve with 3" male Camlock for drainage. Foot operated inflator.

Optional Accessories: Top cover
Ground sheet
Repair kit - cold glue
Repair kit - hot vulcanising

Safety Data: Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 07/11/2018